



TECHNICAL DATASHEET

NC KOMBI

ART. NO: #126.052 (250 g)

NC KOMBI is a one component nitrocellulose stopper used for filling small imperfections such as scratches, pinholes and shallow dents. Thanks to its ultra smooth consistency, it can be applied in very thin coats. After sanding, a pore-free surface is produced which can then be painted without being primed.

FEATURES

- ✓ Easily fills small body imperfections
- ✓ Exceptionally smooth consistency
- ✓ Can be applied in very thin coats
- ✓ Produces a pore-free surface after sanding
- ✓ Can be painted without the need of a primer

APPLICATION

Due to its extremely fine structure, NC KOMBI is recommended to be used as a final surface filler prior to painting. Ideal for touching up minor imperfections, shallow dents, scratches, pinholes and stone-chip damage.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

HANDLING

1. The surface must be clean, dry and grease free. Painted surfaces must be thoroughly sanded. Can be applied directly to a primer provided that the primer is completely dry.
2. Apply the filler in thin layers. For thicker layers apply in stages leaving 30 - 40 minutes between applications.
3. The filler can be wet sanded after 3 hours with a fine grit abrasive paper.
4. A primer coat can be applied or the filler can be painted directly with an acrylic or synthetic resin based lacquer.

VOC INFORMATION		
Category	Putties & Fillers	
	g/L	LBS/GAL
VOC	431.9	3.60
Density	1455	12.14

PRODUCT DATA

Color: Dark Grey

Hardening Time: Approximately 3 hours

Shelf Life: Minimum 6 months at 18 - 20°C (in original container)

Package: 250 g plastic tube

Number per case: 12

Safety Data Sheet (SDS) is available on our website