



TECHNICAL DATASHEET

LUBRI 3000

ART. NO: #380.005 (330 g)

LUBRI 3000 is a multi-purpose synthetic lubricant spray that is safe to use on anything that slides, swivels, rolls or squeaks. It can withstand temperatures within a range of -11°F to 365°F (-24°C to 185°C), and when applied it is temporarily thinned with a solvent that has the ability to clean and penetrate surfaces while carrying the grease to hard to reach areas. Once applied the solvent completely evaporates, leaving behind a thin film of grease that provides long term lubrication that does not evaporate, dry or wash out.

FEATURES

- ✓ Reduces friction
- ✓ Offers long lasting lubrication and protection
- ✓ Protects against rust and corrosion
- ✓ Penetrates and Coats
- ✓ Will not drip, run or evaporate
- ✓ Comes with a 2" applicator straw for easy spray control
- ✓ Silicone free

APPLICATION

Multi-purpose grease ideal for use in automotive, home, marine and industrial applications. Can be applied on hinges, locks, latches, seat tracks, battery terminals, windshield wiper mechanisms, bolts, bearings and more. Can be applied in the home on sliding doors, windows, hinges, appliances, garage door tracks, chains, screws, guns and tools. Ideal for trailer rollers, winches, turnbuckles, shackles, bearings, slides, motor pivot points and all external moving parts in marine applications. Can also be used on machinery, fans, blowers, roller channels, chains, conveyors, bearings, gears, pneumatic tools, blades and bits in shop settings.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Color: Transparent

Temperature Range: - 11°F to 365°C (-24°C to 185°C)

Shelf Life: 2 years

Package: 330 g

Number per case: 12

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C. NOT SUITABLE FOR USE ON PURE WHITE SURFACES.



HANDLING

APPLICATION

1. Shake can vigorously for 1 - 2 minutes before use.



2. Spray on surfaces to be lubricated, protected and penetrated. Use the extension straw to get into hard-to-reach places.