



TECHNICAL DATASHEET

RUSTWORX

ART. NO: #126.028 (300 g)

RUSTWORX is an oil-based spray that penetrates surfaces and creeps under rust, ultimately protecting treated components against corrosion and mechanical abrasion. Can be used to loosen rusted parts such as screws, nuts and door hinges, and doubles as a contact spray.

FEATURES

- ✓ Easy to use aerosol application
- ✓ Penetrates rusted surfaces
- ✓ Loosens difficult screws, nuts and hinges
- ✓ Prevents corrosion and mechanical abrasion

APPLICATION

Ideal for use in automotive, marine, shop, industrial and heavy duty applications.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

HANDLING

1. Shake well before using.
2. Spray the product directly on the parts you wish to loosen.
3. Wait 10 - 15 minutes for reaction time to elapse.

PRODUCT DATA

Nature: Penetrating oil

Color: Brown

Reaction Time: 10 - 15 minutes

Package: 300g

Number per case: 12

Safety Data Sheet (SDS) is available on our website