



TECHNICAL DATASHEET

SILICONE SPRAY

ART. NO: #380.003 (320 g)

SILICONE SPRAY is a multi-purpose product that lubricates, waterproofs and insulates all types of mechanical equipment. Designed to reduce friction and prevent binding and “chattering” of channels, sliders and hinges. Also can be used to protect rubber moldings from extreme weather.

FEATURES

- ✓ Reduces friction
- ✓ Repels dirt and dust
- ✓ Offers long lasting lubrication and protection
- ✓ Protects against water and UV
- ✓ Eliminates squeaks
- ✓ Comes with a 2" applicator straw for easy spray control
- ✓ Safe for use on metal, rubber, vinyl, wood and more

APPLICATION

Can be used to lubricate doors, locks, hinges, belts windows, latches, zippers, tools, sports equipment, lawn equipment, valves, pulleys, fans and more. Equally protects electrical parts such as distributors, ignition wires and spark-plugs and can be used to treat and maintain rubber and plastic surfaces such as rubber moldings, boots, cables, locks, weather stripping and movable components. Ideal for use as a waterproofing agent for automotive, home, marine, and shop usage.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Color: Transparent

Shelf Life: 2 years

Package: 320g

Number per case: 12

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C. NOT SUITABLE FOR USE ON PURE WHITE SURFACES.



HANDLING

APPLICATION

1. Shake can vigorously for 1 - 2 minutes before use.



2. Hold the can 15-20 cm away from surface. Spray the surface, holding can upright while spraying. A light spray should be sufficient for most applications.



3. Wipe away any excess of product.