



TECHNICAL DATASHEET

WHITE LITHIUM GREASE

ART. NO: #380.004 (300 g)

WHITE LITHIUM GREASE is a non-chlorinated, heavy-duty grease that provides excellent multi-purpose lubrication for a wide range of uses. The non-sag, non-splatter formula is great for lubricating while protecting against rust and corrosion in areas that require adhesion and heavier coating.

FEATURES

- ✓ Reduces friction
- ✓ Offers long lasting lubrication and protection
- ✓ Protects against rust and corrosion
- ✓ Will not splatter, melt, run, wash-off or freeze
- ✓ Comes with a 2" applicator straw for easy spray control
- ✓ Silicone free

APPLICATION

Ideal for use in automotive, home, marine, shop, industrial and heavy duty applications. Can be applied on hinges, locks, latches, seat tracks, battery terminals, windshield wiper mechanisms, bolts and bearings. Can be used in the home on sliding doors, windows, appliances, garage door tracks, chains, screws, guns and tools. Ideal for trailer rollers, winches, turnbuckles, shackles, bearings, slides, motor pivot points and all external moving parts in marine applications. Can also be used on machinery, fans, blowers, roller channels, chains, conveyors, bearings, gears, pneumatic tools, blades and bits in shop settings.

CONDITIONS OF USE AND CONFORMITY

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgment in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

HEALTH & SAFETY

See Safety Data Sheet and labels for additional safety information and handling instructions. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry. Wear appropriate PPE such as eye and skin protection. In the event of injury, see first aid procedures on SDS. Always observe all applicable precautions and follow good safety and hygiene practices.

PRODUCT DATA

Color: White

Shelf Life: 2 years

Package: 300g

Number per case: 12

Safety Data Sheet (SDS) is available on our website



TECHNICAL DATASHEET

CAUTION

CONTENTS UNDER PRESSURE. DO NOT STORE AT TEMPERATURES ABOVE 50°C. NOT SUITABLE FOR USE ON PURE WHITE SURFACES.



HANDLING

APPLICATION

1. Shake can vigorously for 1 - 2 minutes before use.
2. Move the part(s) so you have easy access. Remove mechanical parts to get good contact as you apply the lithium grease.
3. Spray WHITE LITHIUM GREASE where needed (anywhere metal might come in contact with other metal).